



WASTOP® INLINE CHECK VALVE

WaStop 183

Model Name	WS183
Nominal Diameter	DN 200
Fasteners mtrl.	EN 1.4404
Gasket	EPDM
Watertightness	EN 13564
Weight [kg]	4
Max. ID Host Pipe [mm]	200
Min. ID Host Pipe [mm]	182
Max. Flow Velocity [m/s]	2
Max. Flow Volume [l/s]	64

Product Variants

Art. No	WS183-S2-316	WS183-S3-316	WS183-S4-316	WS183-C-316
Membrane mtrl.	MVQ Silicone	MVQ Silicone	MVQ Silicone	EPDM
Valve Body	EN 1.4404	EN 1.4404	EN 1.4404	EN 1.4404
Max. Back Pressure [mH ₂ O]	3	5	8	5
Horizontal Opening [mmH ₂ O]	205	235	335	290
Horizontal Closing [mmH ₂ O]	90	100	155	100
Submerged Opening [mmH ₂ O]	175	200	225	200
Submerged Closing [mmH ₂ O]	30	35	45	35
Vertical Opening [mmH ₂ O]	265	315	350	315
Vertical Closing [mmH ₂ O]	165	285	315	285
CO ₂ Equivalent (CO ₂ e) [kg CO ₂ e/unit]	32.1	32.2	32.5	-
Weight [kg]	4.1	4.2	4.2	-

