

# WASTOP® INLINE CHECK VALVE

## WaStop 515

Model Name	WS515
Nominal Diameter	DN 500
Fasteners mtrl.	EN 1.4404
Gasket	EPDM
Weight [kg]	37
Min. ID Host Pipe [mm]	518
Max. ID Host Pipe [mm]	536
Max. Flow Velocity [m/s]	4
Max. Flow Volume [l/s]	833

## Product Variants

Art. No	WS515-S3-304/316	WS515-S4-304/316
Membrane mtrl.	Polyurethane	Polyurethane
Valve Body	EN 1.4301 / EN 1.4404	EN 1.4301 / EN 1.4404
Max. Back Pressure [mH <sub>2</sub> O]	5	8
Horizontal Opening [mmH <sub>2</sub> O]	270	360
Horizontal Closing [mmH <sub>2</sub> O]	165	180
Submerged Opening [mmH <sub>2</sub> O]	185	210
Submerged Closing [mmH <sub>2</sub> O]	55	70
Vertical Opening [mmH <sub>2</sub> O]	400	440
Vertical Closing [mmH <sub>2</sub> O]	240	265
CO <sub>2</sub> Equivalent (CO <sub>2</sub> e) [kg CO <sub>2</sub> e/unit]	200.2	200.3
Weight [kg]	37.3	37.3

